



## Consistently ergonomic from loading to cleaning: TWISTER / TWISTER G

### Technical data:

Max. cut-off length (mm/inch)	1 - 50; $\frac{4}{100}$ " - 2"
Max. cut-off blade speed/minute	300/400 (TWISTER G)
Gridsets (mm/inch)	4/5/6/8/10/12/15/17/ 20/24/30/40/60/120 $\frac{1}{5}$ " ; $\frac{3}{10}$ " ; $\frac{2}{5}$ " ; $\frac{1}{2}$ " ; $\frac{3}{5}$ " ; $\frac{7}{10}$ " ; $\frac{5}{4}$ " ; 1" ; $1\frac{1}{5}$ " ; $1\frac{3}{5}$ " ; $4\frac{7}{10}$ "
Housing dimensions (mm/inch)	
Length with lift and outlet conveyor	1,900; $74\frac{4}{5}$ "
Width with lift and outlet conveyor	1,800; 71"
Height with lift and outlet conveyor	1,280; $50\frac{2}{5}$ "
Weight with lift and outlet conveyor (kg/lb)	approx. 670; 1,477
One-hand operating system	✓
Electronic control	✓
Up to 30 stored cutting programs with user rights allocated over four levels	✓
Cutting statistics (operating data recording)	✓

Accessory trolley on request

### The benefits for you at a glance:

- First-class cutting quality
- Semi-automatic loading
- Easy-to-use lift for E containers (on request)
- Optimum product compression
- Ergonomic one-hand operating system for closing the loading chamber
- Consistently ergonomic even for cleaning
- Precisely portioned dicing and strip cutting/packing units of a prescribed weight (on request)
- Product specific accessories (on request)
- Patented counter direction gridset (on request)

