



MACHINE INFORMATION	XTRAVAC
	<b>640</b>
MACHINE MATERIAL	<b>ALL STAINLESS</b>
MACHINE STYLE	DOUBLE CHAMBER
AMOUNT OF SEALBARS	4
SEALBAR LENGTH INCH	25.5"
SEALBAR LENGTH <b>MM</b>	640 mm
BY-ACTIVE SEALBARS	N/A
HOT WIRE CUT OFF	OPTIONAL
DISTANCE BETWEEN BARS INCH	22.5"
DISTANCE BETWEEN BARS <b>MM</b>	560 mm
VACUUM PUMP (CBH / HP)	100 / 5
GASFLUSH	OPTIONAL / US\$500
CHAMBER HEIGHT INCH	8"
CHAMBER HEIGHT <b>MM</b>	200 mm
MACHINE ON WHEELS	STANDARD
CHAMBER LID MOVEMENT	MANUAL
MACHINE DIMENSIONS INCH	60" x 33" x 40"
MACHINE DIMENSIONS <b>MM</b>	1510x730x1010 mm
CHAMBER DIMENSIONS INCH	29" x 27" X 8"
CHAMBER DIMENSIONS <b>MM</b>	720x675x200 mm
MACHINE CONTROLS	MICRO PROCESSOR
MACHINE WEIGHT <b>KG</b>	425
MACHINE WEIGHT LBS	935
VOLTAGE	220 V 3ph

Distributed by: VC999 Packaging Systems, Kansas City MO  
 Tel. 800-728-2999, Fax 816-472-1999